

## Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 830 LINE-S / L-564MM S-1,5M Index: 19.4179.1611.24



### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Ρ	roo	fuct	inform	ation
	100	JUGL		auon

Category	y Surface mounted luminaires					
Family	X-LINE SLIM LED LINE					
Name	X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 830 LINE-S / L- 564MM S-1,5M					
Index	19.4179.1611.24					
	$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c } \hline \hline \begin{tabular}{ c c c } \hline \hline \begin{tabular}{ c c c } \hline \hline \begin{tabular}{ c c c c } \hline \hline \begin{tabular}{ c c c } \hline \hline \begin{tabular}{ c c c c } \hline \hline \begin{tabular}{ c c c c } \hline \hline \begin{tabular}{ c c c } \hline \hline \begin{tabular}{ c c c c } \hline \hline \begin{tabular}{ c c c } \hline \hline \begin{tabular}{ c c c c c c c } \hline \hline \begin{tabular}{ c c c c c c c c c c c c c c c c c c c$					

## Light and electrical data

	Light source	LED
	Luminous flux LED [lm]	2221
	LED power [W]	10,9
	Luminaire luminous flux [lm]	1643,5
	Power of luminaire [W]	12,8
	Luminaire's light efficiency [lm/W]	128,4
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)



Mechanical data	∏tH ⊨ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA) IK04 564 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       200         45°       300         45°       300         30°       15°         30°       15°         0°       0°         15°       0°         15°       90°

# Accessories

Poland


**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025