

Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 04 840 LINE-S / L-564MM S-1,5M Index: 19.4179.1621.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Light and electrical data

	Family	X-LINE SLIM LED LINE		
	Name	X-LI <mark>NE SLIM</mark> L-DOWN LED 2200 MICRO-PRM E 04 840 LINE-S / L- 564 <mark>MM S-1</mark> ,5M		
	Index	19.4179.1621.04		
			$\textcircled{P} \bigoplus \textcircled{P}_{40} \widecheck{K}_{4} \bigoplus_{\text{indear}} \widecheck{\&}$	Ð
	Light sou	irce	LED	
	Luminous flux LED [lm]		2338	
	LED power [W]		10,9	
Luminaire luminous flux [lm]		1730,1		
	Power of luminaire [W] Luminaire's light efficiency [lm/W] Color of the light [K]		12,8	
			135,2	
			4000	
	CRI		>80	
	SDCM (LED sources)		3	
Beam angle [°] Photobiological risk class (IEC/EN 62471) Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By		igle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°	
		RG0		
		n against electric shock	I	
		IP40		
		220240 V, 5060 Hz		
		100000		
		L80/B10		

5 ÷ 35

>0,95

(C16)

standard on/off (E)

46 (B10), 74 (B16), 72 (C10), 115

Category Surface mounted luminaires

Operating temperature range [°C]

Driver

Power factor $\cos \phi$

Circuit load capacity



Mechanical data	∏H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04 564 x 48 x 70
A graph of light			105° 90° 90° 90° 90° 90° 90° 90° 90

Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

