

Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 840 LINE-S / L-564MM S-1,5M Index: 19.4179.1621.21



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Droduct	information
Product	mormation

	Category	 Surface mounted lumir 	naires	
	Family	X-LINE SLIM LED LINE		
	Name	X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 840 LINE-S / L- 564MM S-1,5M		
	Index	19.4179.1621.21		
				4 Indoor
	Light sou	irce	LED	
	Luminou	s flux LED [lm]	2338	
LED power [W] 10,9 Luminaire luminous flux [lm] 1730,1 Power of luminaire [W] 12,8		ver [W]	10,9	
		1730,1		
		12,8		
	Luminaire's light efficiency [lm/W] Color of the light [K]		135,2	
			4000	
	CRI		>80	
	SDCM (LED sources)		3	

Light and electric

ical data	Light source	LED
	Luminous flux LED [lm]	2338
	LED power [W]	10,9
	Luminaire luminous flux [lm]	1730,1
	Power of luminaire [W]	12,8
	Luminaire's light efficiency [lm/W]	135,2
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor cos φ	>0,95
	Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)



Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) Micro-PRM (micro-prismatic diffuser PMMA) IK04 564 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45

Accessories

Poland


LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025