

Product: X-LINE SLIM L-DOWN LED 4400 PLX E 34 830 LINE-EL / L-1132MM S-1,5M Index: 19.4179.2111.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	auon

Product information	Categor	y Surface mounted luminaires
	Family	X-LINE SLIM LED LINE
	Name	X-LINE SLIM L-DOWN LED 4400 PLX E 34 830 LINE-EL / L-1132MM S-1,5M
	Index	19.4179.2111.34
		$\overbrace{ED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{lador} \bigoplus_{lador} \bigoplus$
Light and electrical data	Light so	urce LED
	Luminou	ıs flux LED [lm] 4442
	LED pov	ver [W] 21,8
	Luminai	re luminous flux [lm] 2842,9

LLD po	ino. [iii]		;•
Luminai	aire luminous flux [[lm]	2842,9
Power of	of luminaire [W]		24,8
Luminai	aire's light efficienc	cy [lm/W]	114,6
Color of	of the light [K]		3000
RI			>80
CM ((LED sources)		3
Beam a	angle [°]		(C0-C180) / (C90-C270) - 96,4° / 90,2°
notobi 2471)	iological risk class	s (IEC/EN	RG0
Protecti	ion against electri	ic shock	I
otecti	ion degree		IP40
oltage	9		220240 V, 5060 Hz
etime	e of LED sources [[h]	100000
/By			L80/B10
erati	ing temperature ra	ange [°C]	5 ÷ 35
river			standard on/off (E)
ower f	factor cos φ		>0,95
Circuit le	load capacity		25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	□tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 1132 x 48 x 70
A graph of light			105° 90° 90° 75° 60° 45° 45° 45° 250 45° 45° 45° 45° 45° 45° 45° 45°




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

