

Product: X-LINE SLIM L-DOWN LED 4400 PLX EDD 04 830 LINE-1EL / L-1132MM S-1,5M Index: 19.4179.2113.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	information
FIGUUCI	mormation

	Category	Surface mounted luminaires
	Family	X-LINE SLIM LED LINE
	Name	X-LINE SLIM L-DOWN LED 4400 PLX EDD 04 830 LINE-1EL / L- 1132MM S-1,5M
	Index	19.4179.2113.04

 $\langle E \rangle$

CE

 \mathbf{P}_{40}

Light and electrical data

Ī	Light source	LED
I	Luminous flux LED [lm]	4442
I	LED power [W]	21,8
I	Luminaire luminous flux [lm]	2842,9
Ī	Power of luminaire [W]	24,8
Ī	Luminaire's light efficiency [lm/W]	114,6
(Color of the light [K]	3000
(CRI	>80
	SDCM (LED sources)	3
I	Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
	Photobiological risk class (IEC/EN 62471)	RG0
I	Protection against electric shock	I
I	Protection degree	IP40
`	Voltage	220240 V, 5060 Hz
I	Lifetime of LED sources [h]	100000
I	Lx/By	L80/B10
(Operating temperature range [°C]	5 ÷ 35
[Driver	DIM DALI (EDD)
I	Power factor cos φ	>0,95
(Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)



Mechanical data	□tH B B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 1132 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 100 45° 200 45° 200 30° 15° 30° 15° 30° 15° 30° 15° 0° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15°


Accessories

Poland

LUXIONA


Index 6E1-500KW041P-5

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025