

Product: X-LINE SLIM L-DOWN LED 4400 MICRO-PRM E 04 830 LINE-EL / L-1132MM S-1,5M Index: 19.4179.2411.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation

Category	Surface mounted luminaires
Family	X-LINE SLIM LED LINE
Name	X-LINE SLIM L-DOWN LED 4400 MICRO-PRM E 04 830 LINE-EL / L- 1132MM S-1,5M
Index	19.4179.2411.04
	$\underbrace{E}_{LED} \bigoplus \underbrace{E}_{E} \bigoplus \underbrace{P}_{40} \underbrace{I}_{K_{4}} \bigoplus \underbrace{I}_{mdoor} \underbrace{I}_{M}$

Light and electrical data

	Light source	LED
I	Luminous flux LED [lm]	4442
I	LED power [W]	21,8
I	Luminaire luminous flux [lm]	3287,1
Ī	Power of luminaire [W]	24,8
Ī	Luminaire's light efficiency [lm/W]	132,5
(Color of the light [K]	3000
(CRI	>80
;	SDCM (LED sources)	3
I	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
I	Protection against electric shock	1
Ī	Protection degree	IP40
`	Voltage	220240 V, 5060 Hz
Ī	Lifetime of LED sources [h]	100000
Ī	Lx/By	L80/B10
(Operating temperature range [°C]	5 ÷ 35
Ī	Driver	standard on/off (E)
	Power factor cos φ	>0,95
(Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data		Assembly	surface mounted on slings
	Ц	Material	aluminum
Α	B	Color	RAL 9005 (black)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1132 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 40° 40° 40° 45° 40° 45° 45° 45° 45° 45° 45° 45° 45

Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

