

# Product: X-LINE SLIM L-DOWN LED 4400 MICRO-PRM EDD 34 840 LINE-1EL / L-1132MM S-1,5M Index: 19.4179.2423.34



### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
1104400		

	Category	Surface mounted luminaires
	Family	X-LINE SLIM LED LINE
	Name	X-LINE SLIM L-DOWN LED 4400 MICRO-PRM EDD 34 840 LINE- 1EL / L-1132MM S-1,5M
	Index	19.4179.2423.34

 $\langle E \rangle$ 

 $\mathbb{IP}_{40}$ 

A

E

### Light and electrical data

	Light source	LED
	Luminous flux LED [Im]	4676
	LED power [W]	21,8
	Luminaire luminous flux [lm]	3460,2
	Power of luminaire [W]	24,8
	Luminaire's light efficiency [lm/W]	139,5
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	DIM DALI (EDD)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)



Mechanical data		Assembly	surface mounted on slings
	Птн	Material	aluminum
L. A	∟ <u></u>  ++  B	Color	RAL 9016 (white)
	В	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1132 x 48 x 70
		Dimensions [mm]	1132 X 48 X 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 40° 40° 40° 40° 40° 40° 40° 40



## Accessories

#### Index 6E1-500KW341P-5 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



#### Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



