

Product: X-LINE SLIM L-DOWN LED 4400 MICRO-PRM E 34 830 LINE-EP / L-1132MM S-1,5M Index: 19.4179.2511.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Category	Surface mounted luminaires	
Family	X-LINE SLIM LED LINE	
Name	X-LI <mark>NE SLIM</mark> L-DOWN LED 4400 MICRO-PRM E 34 830 LINE-EP / L 1132 <mark>MM S</mark> -1,5M	
Index	19.4179.2511.34	
	$\underbrace{}_{\operatorname{LED}} \underbrace{}_{\operatorname{ED}} \underbrace{}_{\operatorname{ED}} _{\operatorname{ED}} _{\operatorname$	Ð

Light and electrical data

	Light source	LED
	Luminous flux LED [lm]	4442
	LED power [W]	21,8
	Luminaire luminous flux [lm]	3287,1
	Power of luminaire [W]	24,8
	Luminaire's light efficiency [lm/W]	132,5
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data		Assembly	surface mounted on slings
	Птн	Material	aluminum
L. A	∟ <u></u> ++ B	Color	RAL 9016 (white)
	В	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1132 x 48 x 70
		Dimensions [mm]	1132 X 48 X 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 40° 40° 40° 40° 40° 40° 40° 40




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

