

Product: X-LINE SLIM L-DOWN LED 6600 PLX E 04 840 LINE-EL / L-1692MM S-1,5M Index: 19.4179.3121.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

Category	gory Surface mounted luminaires		
Family	X-LINE SLIM LED LINE		
Name	X-LINE SLIM L-DOWN LED 6600 PLX E 04 840 LINE-EL / L-1692MM S-1,5M		
Index	19.4179.3121.04		
	$\overbrace{ED} \textcircled{\textcircled{b}} \end{array}{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \end{array}{\textcircled{b}} \rule{\textcircled{b}} \textcircled{\textcircled{b}} \textcircled{\textcircled{b}} \rule{\textcircled{b}} \end{array}{\textcircled{b}} \rule{\textcircled{b}} \rule{\rule{b}} \rule{\rule{b}$		
Light sou			

Light and electrical data

Light source	LED
Luminous flux LED [Im]	7014
LED power [W]	32,7
Luminaire luminous flux [lm]	4489
Power of luminaire [W]	37,2
Luminaire's light efficiency [lm/W]	120,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	∏tH ⊌ B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 2,9 1692 x 48 x 70
A graph of light			105° 0° 0° 0° 90° 90° 90° 75° 0° 75° 60° 100 60° 45° 200 45° 30° 15° 0° 30° 15° 0° 0° 15° 30° 0° 15° 0° 100 15° 30°

Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

