

Product: X-LINE SLIM L-DOWN LED 6600 PLX E 34 840 LINE-EL / L-1692MM S-1,5M Index: 19.4179.3121.34



Description

Protection degree

Power factor $\cos \phi$

Circuit load capacity

Lifetime of LED sources [h]

Operating temperature range [°C]

Voltage

Lx/By

Driver

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuci		anon

Light and electrical data

	Category	Surface mounte	d luminai	ires					
	Family	Family X-LINE SLIM LED LINE							
	Name	X-LINE SLIM L-D S-1,5M	OWN LE	D 6600	PLX E	34 840	LINE-E	L/L-16	692MM
	Index	19.4179.3121.34							
		CE	LED	E		IP ₄₀	K ₀₄	Indoor	
L	Light sou	rce		LI	ED				
	Luminous	s flux LED [lm]		70)14				
	LED pow	er [W]		32	2,7				
	Luminaire	e luminous flux [lm]	44	189				
	Power of	luminaire [W]		37	7,2				
	Luminaire	e's light efficiency [lm/W]	12	20,7				
	Color of t	he light [K]		40	000				
	CRI			>8	30				
	SDCM (L	ED sources)		3					
	Beam an	gle [°]		(C	CO-C180) / (C90)-C270)	- 96,4°	/ 90,2°
	Photobiol 62471)	ogical risk class (II	EC/EN	R	G0				
	Protection	n against electric s	hock	I					

IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

25 (B10), 40 (B16), 39 (C10), 62



Mechanical data	∏tH ⊨→ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 1692 x 48 x 70
A graph of light			$105^{\circ} \qquad 109^{\circ} \qquad 90^{\circ} \qquad$




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

