

# Product: X-LINE SLIM L-DOWN LED 6600 PLX E 04 840 LINE-EP / L-1692MM S-1,5M Index: 19.4179.3221.04



### Description

Driver

Power factor  $\cos \phi$ 

Circuit load capacity

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Light and electrical data

	J				
	Family	Family X-LINE SLIM LED LINE			
	Name	JameX-LINE SLIM L-DOWN LED 6600 PLX E 04 840 LINE-EP / L-1692MM S-1,5M			
	Index	19.4179.3221.04			
			$\begin{array}{c} \\ \\ \\ \\ \\ \\ \end{matrix}} \end{array} \qquad \begin{array}{c} \\ \\ \\ \\ \\ \end{matrix}} \end{array} \qquad \begin{array}{c} \\ \\ \\ \\ \\ \end{matrix}} \end{array} \qquad \begin{array}{c} \\ \\ \\ \\ \\ \end{matrix}} \end{array} \qquad \begin{array}{c} \\ \\ \\ \\ \\ \end{matrix}} \end{array} \qquad \begin{array}{c} \\ \\ \\ \\ \\ \end{matrix}} \end{array} \qquad \begin{array}{c} \\ \\ \\ \\ \end{array}} \qquad \begin{array}{c} \\ \\ \\ \end{array}} \qquad \begin{array}{c} \\ \\ \\ \end{array}} \qquad \begin{array}{c} \\ \\ \end{array} \qquad \begin{array}{c} \\ \end{array} \qquad \begin{array}{c} \\ \end{array}} \qquad \begin{array}{c} \\ \\ \end{array}} \qquad \begin{array}{c} \end{array}} \end{array}} \qquad \begin{array}{c} \end{array}} \qquad \begin{array}{c} \end{array}} \end{array}} \qquad \begin{array}{c} \end{array}} \end{array}} \qquad \begin{array}{c} \end{array}} \end{array}}$		
	Light so	urce	LED		
	Luminou	us flux LED [lm]	7014		
	LED pov	wer [W]	32,7		
	Luminai	re luminous flux [lm]	4489		
	Power of luminaire [W] Luminaire's light efficiency [Im/W]		37,2		
			/] 120,7		
	Color of	the light [K]	4000		
	CRI SDCM (LED sources) Beam angle [°]		>80		
			3		
			(C0-C180) / (C90-C270) - 96,4° / 90,2°		
Photobiological risk class (IEC/EN 62471) Protection against electric shock Protection degree		ological risk class (IEC/E	N <b>RG0</b>		
		on against electric shock			
		on degree	IP40		
	Voltage		220240 V, 5060 Hz		
	Lifetime	of LED sources [h]	100000		
	Lx/By		L80/B10		
	Operatir	ng temperature range [°	C] <b>5</b> ÷ <b>35</b>		

standard on/off (E)

25 (B10), 40 (B16), 39 (C10), 62

>0,95

(C16)

Category Surface mounted luminaires



Mechanical data	∏tH ⊌	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 2,9 1692 x 48 x 70
A graph of light			105° 0° 0°   90° 90°   75° 0°   60° 100   45° 200   45° 200   300 15°   300 15°   0° 15°

## Accessories

Poland

**LUXIONA** 


## Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

