

Product: X-LINE SLIM L-DOWN LED 6600 PLX E 04 840 LINE-S / L-1684MM S-1,5M Index: 19.4179.3321.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	informa	ation

Light and electrical data

Cate	gory Surface m	ounted lumina	aires				
Fami	y X-LINE SLI	M LED LINE					
Name	e X-LINE SLI S-1,5M	M L-DOWN L	ED 6600 PLX E	04 840 I	_INE-S / I	16841	MM
Index	19.4179.33	21.04					
				IP ₄₀		Indoor	Ì
Light	source		LED				
Lumi	nous flux LED [In	ן]	7014				
	CONTRACT DAG		22.7				

LED power [W]	32,7
Luminaire luminous flux [lm]	4489
Power of luminaire [W]	37,2
Luminaire's light efficiency [lm/W]	120,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
rotection degree	IP40
/oltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 2,9 1684 x 48 x 70
A graph of light			$\int_{CO-C180}^{105^{\circ}} \int_{CO-C270}^{105^{\circ}} \int_{CO-C270}^{105^{\circ}$

Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

