

## Product: X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 24 830 LINE-EP / L-1692MM S-1,5M Index: 19.4179.3511.24



## Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

(C16)

Product	inform	ation
1104400		

Product information	Category Surface mounted luminaires		
	Family	X-LINE SLIM LED LINE	
	Name	X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 24 830 LINE-EP / L- 1692MM S-1,5M	
	Index	19.4179.3511.24	
		$\overbrace{ED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{ndoor} \bigoplus_{ndoor} \bigoplus$	
Light and electrical data		urce LED	
	0		
J	Ū	IS flux LED [Im] 6663	
	Ū	us flux LED [lm] 6663	
	Luminou LED pov	us flux LED [lm] 6663	
J	Luminou LED pov Luminain	Is flux LED [lm]         6663           ver [W]         32,7	

Luminaire luminous flux [Im]	4930,6
Power of luminaire [W]	37,2
Luminaire's light efficiency [lm/W]	132,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62



Mechanical data		Assembly	surface mounted on slings
	ЩЩН	Material	aluminum
Α	l⊷+l B	Color	anodised aluminum
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1692 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 300 45° 45° 45° 45° 45° 45° 45° 45° 45° 45°

# Accessories

Poland

**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 07-05-2025