

Product: X-LINE SLIM UP&DOWN LED 8800/8800 PC/MICRO-PRM EDD 04 830 / L-2258mm S-1,5M

Index: 19.4180.6113.04



Description

The luminaire is made of aluminum profile. Its characteristic feature is the light distribution in the upper and lower half-space. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PC and Micro-PRM opal diffuser (intended only for the lower beam) or PC and lenses (intended only for the lower beam). All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions. LED sources distributing light in both the lower and upper half-space are connected into one circuit and use a common, single power supply.

Product information

Category	Surface mounted luminaires
Family	X-LINE SLIM UP&DOWN LED
Name	X-LINE SLIM UP&DOWN LED 8800/8800 PC/MICRO-PRM EDD 04 830 / L-2258mm S-1,5M
Index	19.4180.6113.04
EAN	5902107568986
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	17768
LED power [W]	87,2
Luminaire luminous flux [lm]	12793
Power of luminaire [W]	99,1
Luminaire's light efficiency [lm/W]	129,1
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED courses [h]	100000
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Lx/By	L80/B10
Lx/By Operating temperature range [°C]	L80/B10 5 ÷ 35



Mechanical data		Assembly	surface mounted on slings
	□ th	Material	aluminum
A	B	Color	RAL 9005 (black)
		Diffuser	PC/Micro-PRM (opalescent polycarbonate/micro-prismatic diffuser PMMA) [up/down]
		Impact resistant	IK04
		Dimensions [mm]	2258 x 48 x 70

A graph of light





Accessories

Index 6E1-500KW04K-5

Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 5X SET



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT




Index 6E1-8670-B-1,5-5X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 5X 1-POINT




Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWB04K-5

Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 5X SET

