

Product: X-LINE SLIM SURFACE LED 5200 MICRO-PRM E 34 830 / L-2258MM

Index: 19.4183.4111.34



Description

The luminaire is made of aluminum profile. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on ceiling.

Product information

| Category | Surface mounted luminaires |
|----------|--|
| Family | X-LINE SLIM SURFACE LED |
| Name | X-LINE SLIM SURFACE LED 5200 MICRO-PRM E 34 830 / L-2258MM |
| Index | 19.4183.4111.34 |
| EAN | 5902107559861 |















Light and electrical data

| Light source | LED |
|---|---|
| Luminous flux LED [lm] | 5076 |
| LED power [W] | 24,8 |
| Luminaire luminous flux [lm] | 3756,2 |
| Power of luminaire [W] | 28,2 |
| Luminaire's light efficiency [lm/W] | 133,2 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 88,4° / 86° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP40 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 35 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 25 (B10), 40 (B16), 39 (C10), 62 (C16) |



| Mechanical data | | Assembly | surface mounted on ceiling |
|-----------------|----|------------------|---|
| | ‡н | Material | aluminum |
| A | B | Color | RAL 9016 (white) |
| | | Diffuser | Micro-PRM (micro-prismatic diffuser PMMA) |
| | | Impact resistant | IK04 |
| | | Dimensions [mm] | 2258 x 48 x 70 |

A graph of light







