

**Product:** X-LINE SLIM SURFACE LED 2600 MICRO-PRM EDD 34 840 / L-1138MM

**Index:** 19.4183.1123.34



## Description

The luminaire is made of aluminum profile. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on ceiling. \*Selected luminary variants are available with ENEC certificate.

## Product information

|          |  |
|----------|--|
| Category | Surface mounted luminaires                                   |
| Family   | X-LINE SLIM SURFACE LED                                      |
| Name     | X-LINE SLIM SURFACE LED 2600 MICRO-PRM EDD 34 840 / L-1138MM |
| Index    | 19.4183.1123.34  |

## Light and electrical data

|   |                                      |
|---|--------------------------------------|
| Light source                              | LED                                  |
| Luminous flux LED [lm]                    | 2672                                 |
| LED power [W]                             | 12,4                                 |
| Luminaire luminous flux [lm]              | 1977,3                               |
| Power of luminaire [W]                    | 14,1                                 |
| Luminaire's light efficiency [lm/W]       | 140,2                                |
| Color of the light [K]                    | 4000                                 |
| CRI                                       | >80                                  |
| SDCM (LED sources)                        | 3                                    |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 88,4° / 86° |
| Photobiological risk class (IEC/EN 62471) | RG0                                  |
| Protection against electric shock         | I                                    |
| Protection degree                         | IP40                                 |
| Voltage                                   | 220..240 V, 50..60 Hz                |
| Lifetime of LED sources [h]               | 100000                               |
| Lx/By                                     | L80/B10                              |
| Operating temperature range [°C]          | 5 ÷ 35                               |
| Driver                                    | DIM DALI (EDD)                       |

**Mechanical data**



|                  |   |
|------------------|---|
| Assembly         | surface mounted on ceiling                |
| Material         | aluminum                                  |
| Color            | RAL 9016 (white)                          |
| Diffuser         | Micro-PRM (micro-prismatic diffuser PMMA) |
| Impact resistant | IK04                                      |
| Dimensions [mm]  | 1138 x 48 x 70                            |

**A graph of light**

