

Product: X-LINE SLIM SURFACE LED 3900 MICRO-PRM E 34 840 / L-1698MM

Index: 19.4183.2121.34



Description

The luminaire is made of aluminum profile. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on ceiling. *Selected luminary variants are available with ENEC certificate.

Product information

| | |
|----------|--|
| Category | Surface mounted luminaires |
| Family | X-LINE SLIM SURFACE LED |
| Name | X-LINE SLIM SURFACE LED 3900 MICRO-PRM E 34 840 / L-1698MM |
| Index | 19.4183.2121.34 |

Light and electrical data

| | |
|---|--------------------------------------|
| Light source | LED |
| Luminous flux LED [lm] | 4008 |
| LED power [W] | 18,6 |
| Luminaire luminous flux [lm] | 2965,9 |
| Power of luminaire [W] | 21,1 |
| Luminaire's light efficiency [lm/W] | 140,6 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 88,4° / 86° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP40 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 35 |
| Driver | standard on/off (E) |

Mechanical data



| | |
|------------------|---|
| Assembly | surface mounted on ceiling |
| Material | aluminum |
| Color | RAL 9016 (white) |
| Diffuser | Micro-PRM (micro-prismatic diffuser PMMA) |
| Impact resistant | IK04 |
| Dimensions [mm] | 1698 x 48 x 70 |

A graph of light

