

Product: X-LINE SLIM L-DOWN LED COMPACT 4000 PLX EDD 04 830 / L-1138MM S-1,5M

Index: 19.4190.1213.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting on suspensions. There is the possibility of fitting a luminaire with a sound-absorbing housing.

Product information

| Category | Compact |
|----------|--|
| Family | X-LINE SLIM LED COMPACT |
| Name | X-LINE SLIM L-DOWN LED COMPACT 4000 PLX EDD 04 830 / L- 1138MM S-1,5M |
| Index | 19.4190.1213.04 |
| EAN | 5902107321857 |















Light and electrical data


| Light source | LED |
|---|---|
| Luminous flux LED [lm] | 4280,2 |
| LED power [W] | 22,2 |
| Luminaire luminous flux [lm] | 2739,3 |
| Power of luminaire [W] | 25,2 |
| Luminaire's light efficiency [lm/W] | 108,7 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 96,4° / 90,2° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP40 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 90000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 35 |
| Driver | DIM DALI (EDD) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 17 (B10), 28 (B16), 26 (C10), 41 (C16) |



| Mechanical data | Assembly | surface mounted on slings |
|-----------------|------------------|---------------------------|
| | H Material | aluminum |
| A B | Color | RAL 9005 (black) |
| | Diffuser | PLX (PMMA opal) |
| | Impact resistant | IK04 |
| | Weight [kg] | 3,2 |

Dimensions [mm]

A graph of light



1138 x 48 x 70





Accessories

Index 6E1-500KW04K-5

Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 5X SET



Index 6E1-8670-B-1,5-5X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 5X 1-



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT




Index 19.3272.1205.00

Index 19.4089.0004.00

Name X-LINE SLIM SOUND

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.4089.0005.00

Index 6E1-500KWB04K-5

Name SUSPENSION NEW TYPE-A+E 04


LENGHT 1,5M WIRE 5X SET

Name X-LINE SLIM SOUND ABSORBENT L-1138MM BLUE



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Index 19.4089.0006.00

Name x-LINE SLIM SOUND ABSORBENT L-1138MM GREY







ABSORBENT L-1138MM RED

