


Product: X-LINE SLIM L-DOWN LED COMPACT 4000 MICRO-PRM E 04 830 / L-1418MM S-1,5M Index: 19.4190.2111.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting on suspensions.

Product information		Category Compact			
		Family	X-LINE SLIM LED COMPACT		
		Name	X-LINE SLIM L-DOWN LED COMPACT 4000 MICRO-PRM E 04 830 / L-1418MM S-1,5M		
		Index	19.4190.2111.04		
		EAN	5902107554606		
			$\begin{array}{c} \hline \hline$		
Light and electrical data		Light sou	burce LED		
		Luminous	bus flux LED [Im] 4524		
		LED pow	wer [W] 23		
		Luminair	ire luminous flux [Im] 3347,8		
		Power of	of luminaire [W] 26,1		
		Luminair	ire's light efficiency [lm/W] 128,3		
		Color of t	f the light [K] 3000		
		CRI	>80		
		SDCM (L	(LED sources) 3		
		Beam an			
		Photobio 62471)	iological risk class (IEC/EN RG0		
		Protectio	ion against electric shock I		
		Protectio	ion degree IP40		
		Voltage	220240 V, 5060 Hz		
		Lifetime of	e of LED sources [h] 90000		
		Lx/By	L80/B10		
		Operating	ing temperature range [°C] 5 ÷ 35		
		Driver	standard on/off (E)		
		Power fa	factor cos φ >0,95		
		Circuit loa	load capacity 25 (B10), 40 (B16), 39 (C10), 62 (C16)		



Mechanical data	∏ H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04 1418 x 48 x 70
A graph of light			105° 90° 90° 90° 90° 90° 90° 90° 90




Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

