


Product: X-LINE SLIM L-DOWN LED COMPACT 4000 MICRO-PRM EDD 04 830 / L-1418MM S-1,5M Index: 19.4190.2113.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting on suspensions.

Product information	Category Compact		
	Family X-LINE SLIM LED COMPACT		
	Name X-LINE SLIM L-DOWN LED COMPACT 4000 MICRO-PRM EDD 04 830 / L-1418MM S-1,5M		
	Index 19.4190.2113.04		
	EAN 5902107554620		
	$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c c } \hline \begin{tabular}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c c c c c c c c c c c c c c$		
Light and electrical data	Light source LED		
	Luminous flux LED [lm] 4524		
	LED power [W] 23		
	Luminaire luminous flux [Im] 3347,8		
	Power of luminaire [W] 26,1		
	Luminaire's light efficiency [lm/W] 128,3		
	Color of the light [K] 3000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86°		
	Photobiological risk class (IEC/EN RG0 62471)		
	Protection against electric shock		
	Protection degree IP40		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 90000		
	Lx/By L80/B10		
	Operating temperature range [°C] 5 ÷ 35		
	Driver DIM DALI (EDD)		
	Power factor $\cos \varphi$ >0,95		
	Circuit load capacity 17 (B10), 28 (B16), 26 (C10), 41 (C16)		



Mechanical data	∏tH ∎ B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04 2,7 1418 x 48 x 70
A graph of light			$105^{\circ} \qquad 109^{\circ} \qquad 90^{\circ} \qquad$




Accessories

- Index 6E1-500KW04K-5
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT








Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB04K-5
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 5X SET





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025