


Product: X-LINE SLIM L-DOWN LED COMPACT 4000 MICRO-PRM E 04 840 / L-1418MM S-1,5M Index: 19.4190.2121.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting on suspensions.

Product information	C	Category Compact			
	Fa	mily	X-LINE SLIM LED COMPACT		
	N		e X-LINE SLIM L-DOWN LED COMPACT 4000 MICRO-PRM E 04 840 / L-1418MM S-1,5M		
	In	dex	19.4190.2121.04		
	E	AN .	5902107318833		
Light and electrical data	Li	ght sour	burce LED		
	Lu	minous	us flux LED [lm] 4712		
	LE	D powe	wer [W] 23		
	Lu	minaire	ire luminous flux [lm] 3486,9		
	P	wer of I	of luminaire [W] 26,1		
	L	minaire	ire's light efficiency [lm/W] 133,6		
	C	olor of th	f the light [K] 4000		
	С	રા	>80		
	SI	DCM (LE	(LED sources) 3		
	Be	am ang	ungle [°] (C0-C180) / (C90-C270) - 88,4° / 86°		
		otobiolo 471)	iological risk class (IEC/EN RG0		
	Pi	otection	ion against electric shock I		
	Pi	otection	ion degree IP40		
	Vo	ltage	220240 V, 5060 Hz		
	Li	etime o	e of LED sources [h] 90000		
	L>	/By	L80/B10		
	0	perating	ng temperature range [°C] 5 ÷ 35		
	D	iver	standard on/off (E)		
	P	wer fac	actor cos φ >0,95		
	C	rcuit loa	oad capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16)		



Mechanical data	⊟H ⊭⊷ B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04 2,05 1418 x 48 x 70
A graph of light			$los \\ los \\$




Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

