


Product: X-LINE SLIM L-DOWN LED COMPACT 4000 PLX E 04 840 / L-1418MM S-1,5M Index: 19.4190.2221.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting on suspensions.

| Product information | Category Compact |
|---------------------------|--|
| | Family X-LINE SLIM LED COMPACT |
| | Name X-LINE SLIM L-DOWN LED COMPACT 4000 PLX E 04 840 / L- 1418MM S-1,5M |
| | Index 19.4190.2221.04 |
| | EAN 5902107318826 |
| | $\begin{array}{c} \hline \\ \hline $ |
| Light and electrical data | Light source LED |
| | Luminous flux LED [Im] 4712 |
| | LED power [W] 23 |
| | Luminaire luminous flux [lm] 3015,7 |
| | Power of luminaire [W] 26,1 |
| | Luminaire's light efficiency [lm/W] 115,5 |
| | Color of the light [K] 4000 |
| | CRI >80 |
| | SDCM (LED sources) 3 |
| | Beam angle [°] (C0-C180) / (C90-C270) - 96,4° / 90 |
| | Photobiological risk class (IEC/EN RG0 62471) |
| | Protection against electric shock |
| | Protection degree IP40 |
| | Voltage 220240 V, 5060 Hz |
| | Lifetime of LED sources [h] 90000 |
| | Lx/By L80/B10 |
| | Operating temperature range [°C] 5 ÷ 35 |
| | Driver standard on/off (E) |
| | Power factor $\cos \varphi$ >0,95 |
| | Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) |



| Mechanical data | H B | Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm] | surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 2,05 1418 x 48 x 70 |
|------------------|--------|---|---|
| A graph of light | | | $\int_{0}^{10^{\circ}} \int_{0}^{10^{\circ}} \int_{0$ |




Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET




- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

