


Product: X-LINE SLIM L-DOWN LED COMPACT 6000 MICRO-PRM E 04 830 / L-1418MM S-1,5M

Index: 19.4190.3111.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting on suspensions.

Product information

Category	Compact
Family	X-LINE SLIM LED COMPACT
Name	X-LINE SLIM L-DOWN LED COMPACT 6000 MICRO-PRM E 04 830 / L-1418MM S-1,5M
Index	19.4190.3111.04
EAN	5902107369927















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	6149	
LED power [W]	32,5	
Luminaire luminous flux [lm]	4550,3	
Power of luminaire [W]	36,9	
Luminaire's light efficiency [lm/W]	123,3	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP40	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	90000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 35	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)	



Mechanical data		Assembly	surface mounted on slings
	□ th	Material	aluminum
A	l→ B	Color	RAL 9005 (black)
		Diffuser	Micro-PRM (micro-prismatic diffuser F
		Impact resistant	IKUA

Color RAL 9005 (black)

Diffuser Micro-PRM (micro-prismatic diffuser PMMA)


Impact resistant IK04

Weight [kg] 2,53

Dimensions [mm] 1418 x 48 x 70

A graph of light







Accessories

Index 6E1-500KW04K-3

Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 3X 1-POINT




Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWB04K-3

Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

