

Product: X-LINE SLIM SURFACE LED COMPACT 4000 PLX EDD 34 830 / L-1418MM

Index: 19.4191.2213.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting directly to ceiling.

Product information

Category	Compact
Family	X-LINE SLIM SURFACE LED COMPACT
Name	X-LINE SLIM SURFACE LED COMPACT 4000 PLX EDD 34 830 / L-1418MM
Index	19.4191.2213.34
EAN	5902107563035



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4524
LED power [W]	23
Luminaire luminous flux [lm]	2895,4
Power of luminaire [W]	26,1
Luminaire's light efficiency [lm/W]	110,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1418 x 48 x 70

A graph of light

