

Product: FASAD WALL LED 4400 SH SYM FLOOD E 83 IP65 830 / L-1180mm

Index: 19.4193.4111.83



Description

Weather proof powder painted aluminum housing. Clear stainless steel diffuser. Luminaire is equipped with adjustment allowing proper light flux operation. LED panels are applied as light sources. Recommended for walls and solid base. Fasad Wall LED is dedicated to illuminate walls of architectural objects.

Product information

Category	Outdoor luminaires
Family	FASAD WALL LED
Name	FASAD WALL LED 4400 SH SYM FLOOD E 83 IP65 830 / L-1180mm
Index	19.4193.4111.83
EAN	5901867488466














Light and electrical data

Light source	LED
Luminous flux LED [lm]	4406
LED power [W]	23,4
Luminaire luminous flux [lm]	4136
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	167,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 66° / 95°
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 24 (B16), 24 (C10), 40 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 7015 (grey)
Diffuser	SH (transparent hardened glass)
Impact resistant	IK09
Weight [kg]	4
Dimensions [mm]	1180 x 62 x 114



A graph of light

