

**Product:** FASAD WALL LED 650 SH SYM MEDIUM E 83 IP65 840 / L-364mm

**Index:** 19.4193.1221.83



## Description

Weather proof powder painted aluminum housing. Clear stainless steel diffuser. Luminaire is equipped with adjustment allowing proper light flux operation. LED panels are applied as light sources. Recommended for walls and solid base. Fasad Wall LED is dedicated to illuminate walls of architectural objects.

## Product information

Category	Outdoor luminaires
Family	FASAD WALL LED
Name	FASAD WALL LED 650 SH SYM MEDIUM E 83 IP65 840 / L-364mm
Index	19.4193.1221.83
EAN	5902107008451



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	710
LED power [W]	4
Luminaire luminous flux [lm]	629
Power of luminaire [W]	4
Luminaire's light efficiency [lm/W]	157,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 52,4° / 94,8°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 27 (B16), 27 (C10), 44 (C16)

**Mechanical data**



Assembly	mounted on wall
Material	aluminum
Color	RAL 7015 (grey)
Diffuser	SH (transparent hardened glass)
Impact resistant	IK09
Weight [kg]	1,58
Dimensions [mm]	364 x 62 x 114

**A graph of light**

