

**Product:** FASAD WALL LED 1100 SH SYM FLOOD E 83 IP65 830 / L-364mm

**Index:** 19.4193.2111.83



## Description

Weather proof powder painted aluminum housing. Clear stainless steel diffuser. Luminaire is equipped with adjustment allowing proper light flux operation. LED panels are applied as light sources. Recommended for walls and solid base. Fasad Wall LED is dedicated to illuminate walls of architectural objects.

## Product information


Category	Outdoor luminaires
Family	FASAD WALL LED
Name	FASAD WALL LED 1100 SH SYM FLOOD E 83 IP65 830 / L-364mm
Index	19.4193.2111.83
EAN	5902107008406



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	1103
LED power [W]	6
Luminaire luminous flux [lm]	1035
Power of luminaire [W]	7
Luminaire's light efficiency [lm/W]	147,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 66° / 95°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)

**Mechanical data**



Assembly	<b>mounted on wall</b>
Material	<b>aluminum</b>
Color	<b>RAL 7015 (grey)</b>
Diffuser	<b>SH (transparent hardened glass)</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>364 x 62 x 114</b>

**A graph of light**

