

Product: FASAD ODL04 LED 2000 SHM E 20 IP67 840

Index: 19.4194.1221.20



Description

Suitable for ground installation. Pressure-injected aluminum die cast housing, corrosion- resisting, hardened glass diffuser of 10 mm thick, INOX stainless steel outer ring. Ring mounting to the housing is performed with the aid of stainless steel screws. Optic composes high level performance anodized aluminum. Silicone gaskets ensure life-span and exploitation. Luminaires delivered with mounting housing included. The luminaire is equipped with a 3 x 1.5 mm² power wire with a length of 1.5 m. Resistance to static load 2000 kg. Luminaire recommended for architectural and natural objects.

Product information

Category	Outdoor luminaires
Family	FASAD ODL04 LED
Name	FASAD ODL04 LED 2000 SHM E 20 IP67 840
Index	19.4194.1221.20
EAN	5902107035150



Light and electrical data


Light source	LED
Luminous flux LED [lm]	2430
LED power [W]	18
Luminaire luminous flux [lm]	2186
Power of luminaire [W]	23
Luminaire's light efficiency [lm/W]	95
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	2
Beam angle [°]	(C0-C180) / (C90-C270) - 71,6° / 71,6°
Protection against electric shock	I
Protection degree	IP67
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	68000
Lx/By	L90/B10
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	29 (B10), 47 (B16), 49 (C10), 79 (C16)

Mechanical data



Assembly	into the ground
Material	aluminum
Color	INOX
Diffuser	SHM (hardened mat glass)
Impact resistant	IK10
Weight [kg]	4,77
Dimensions [mm]	Ø220 x 300

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%.
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 13-01-2026