

Product: DOMINO LOW UGR LED 4200 RASTER DAISY-BLACK-WIDE EDD 34 830 / 1196X75MM

Index: 19.4100.5213.34



Description

LED luminaire dedicated to be mounted on suspended modular ceilings or cardboard suspended ceilings (using mounting clips or adaptive frame). Equipped with highly efficient LED light sources. The Domino LOW UGR LED uses an anti-glare louvre which reduces glare and directs light precisely. Housing made of steel sheet. Standard colour of the luminaire is white. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80.

Product information


Category	Recessed luminaires
Family	DOMINO LOW UGR LED
Name	DOMINO LOW UGR LED 4200 RASTER DAISY-BLACK-WIDE EDD 34 830 / 1196X75MM
Index	19.4100.5213.34
EAN	5902107301620



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4128
LED power [W]	22,6
Luminaire luminous flux [lm]	3425
Power of luminaire [W]	25,3
Luminaire's light efficiency [lm/W]	135,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°
Protection against electric shock	II
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	50 (B10), 80 (B16), 61 (C10), 98 (C16)

Mechanical data



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	RASTER (anti-glare louver)
Impact resistant	IK04
Dimensions [mm]	1196 x 75 x 50
Mounting hole [mm]	1175 x 65

A graph of light



Accessories

Index	19.3200.0001.00
Name	DOMINO LOW UGR LED 2100/4200/6300 UCHWYTY G/K KPL. / 596X596 / 596X296 / 1196X75 / 596X75

