

Product: DOMINO LOW UGR LED 8400 RASTER DAISY-BLACK-WIDE E 34 830 / 1196X296MM

Index: 19.4100.3411.34



Description

LED luminary dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using mounting clips or adaptive frame), directly on the ceiling (using ceiling sheet) or using ceiling sheet and suspensions. Equipped with highly efficient LED light sources. The Domino LOW UGR LED uses an anti-glare louvre which reduces glare and directs light precisely. Housing made of steel sheet. Standard colour of the luminary is white. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80.

Product information

Category Recessed luminaires

Family DOMINO LOW UGR LED

Name DOMINO LOW UGR LED 8400 RASTER DAISY-BLACK-WIDE E 34 830 / 1196X296MM

Index 19.4100.3411.34
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	8257,3
LED power [W]	45,2
Luminaire luminous flux [lm]	6852
Power of luminaire [W]	50,6
Luminaire's light efficiency [lm/W]	135,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°
Protection against electric shock	II
i Totection against electric shock	II .
Protection degree	IP20
	•
Protection degree	IP20
Protection degree Voltage	IP20 220240 V, 5060 Hz
Protection degree Voltage Lifetime of LED sources [h]	IP20 220240 V, 5060 Hz 100000 (1) / 147000 (2)
Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP20 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B10 (2)
Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP20 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B10 (2) 5 ÷ 30


Mechanical data



Assembly	mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	RASTER (anti-glare louvre)
Impact resistant	IK04
Dimensions [mm]	1196 x 296 x 23
Mounting hole [mm]	1210 x 310



A graph of light







Accessories

Index 19.3200.0003.34

Name DOMINO LOW UGR LED 8400 adaptive frame for plasterboard ceilings 34 / 1196X296



Index 19.3200.0008.34

Name DOMINO LOW UGR LED ceiling sheet-suspension E 34 / 1196X296MM




Index 19.3272.0101.34

Name SUSPENSION NEW TYPE-G+H 34 LENGHT 1,5M WIRE 3X SET TYPE-Y



Index 6E1-500KW341P-3Y

Name SUSPENSION NEW TYPE-G 34 LENGHT 1,5M WIRE 3X 1-POINT TYPE-Y



Index 6E1-8670-B-Y-1,5

Name SUSPENSION NEW TYPE-L LENGHT-1,5 METER WITHOUT WIRE 1-POINT TYPE-Y





