

Product: RUBIN CLEAN CLASS 3-4 LED 11000 SLMR EDD IP65 34 830 KRG5DK / 620X620MM

Index: 19.4107.4713.34



Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 3-4. Surface mounted luminary equipped in highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame.

Product information

Category	Clean Class 3-9
Family	RUBIN CLEAN CLASS 3-4 LED
Name	RUBIN CLEAN CLASS 3-4 LED 11000 SLMR EDD IP65 34 830 KRG5DK / 620X620MM
Index	19.4107.4713.34
EAN	5902107857264
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	11104
LED power [W]	54,5
Luminaire luminous flux [lm]	8161
Power of luminaire [W]	61
Luminaire's light efficiency [lm/W]	133,8
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Driver Power factor cos φ	DIM DALI (EDD) >0,95



Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SLMR (laminated anti-reflective mat glass)
Impact resistant	IK08
Dimensions [mm]	620 x 620 x 78

A graph of light



