

Product: RUBIN CLEAN CLASS 3-4 LED 17600 SLMR EDD IP65 34 830 KRG5DK / 1220X620MM

Index: 19.4107.6913.34



Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 3-4. Surface mounted luminary equipped in highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame.

Product information

Category	Clean Class 3-9
Family	RUBIN CLEAN CLASS 3-4 LED
Name	RUBIN CLEAN CLASS 3-4 LED 17600 SLMR EDD IP65 34 830 KRG5DK / 1220X620MM
Index	19.4107.6913.34
EAN	5902107572655















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	17766	
LED power [W]	87,2	
Luminaire luminous flux [lm]	13058	
Power of luminaire [W]	97,7	
Luminaire's light efficiency [lm/W]	133,7	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
operating temperature range [o]		
Driver	DIM DALI (EDD)	
1 0 1 0 1 1	DIM DALI (EDD) >0,95	



Mechanical data		Assembly	surface mounted on ceiling
		Material	steel sheet
		Color	RAL 9016 (white)
l B		Diffuser	SLMR (laminated anti-reflective mat glass)
	‡H	Impact resistant	IK08
A		Dimensions [mm]	1220 x 620 x 78

A graph of light







