


Product: RUBIN CLEAN CLASS 3-4 NO FRAME LED 5200 SLMR EDD IP65 34 830 KRG5DK / 1174X274MM

Index: 19.4108.1113.34



## **Description**

Luminary dedicated for the clean rooms of increased cleanliness class ISO 3-4. Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

### **Product information**

Category	Clean Class 3-9
Family	RUBIN CLEAN CLASS 3-4 NO FRAME LED
Name	RUBIN CLEAN CLASS 3-4 NO FRAME LED 5200 SLMR EDD IP65 34 830 KRG5DK / 1174X274MM
Index	19.4108.1113.34
EAN	5902107572914
















## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	5076	
LED power [W]	24,8	
Luminaire luminous flux [lm]	3731	
Power of luminaire [W]	27,8	
Luminaire's light efficiency [lm/W]	134,2	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Drataction degree	IP65	
Protection degree	IP65	
Voltage	IP65 220240 V, 5060 Hz	
Voltage	220240 V, 5060 Hz	
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000	
Voltage Lifetime of LED sources [h] Lx/By	220240 V, 5060 Hz 100000 L80/B10	
Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	220240 V, 5060 Hz 100000 L80/B10 5 ÷ 30	



Mechanical data			Assembly	surface mounted on ceiling
	1	В	Material	steel sheet
			Color	RAL 9016 (white)
	В		Diffuser	SLMR (laminated anti-reflective mat glass)
		TH.	Impact resistant	IK08
A	<del></del>		Dimensions [mm]	1174 x 274 x 69

# A graph of light



### **Accessories**

Index 6BZBO60980

Name Handle for pane opening

