

Product: RUBIN CLEAN CLASS 5-6 LED 6500 MICRO-PRM SH EDD IP65 34 840 KRG5DK / 620X620MM

Index: 19.4109.1223.34



## Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Surface mounted luminary equipped in highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame.

## Product information


Category	Clean Class 3-9
Family	RUBIN CLEAN CLASS 5-6 LED
Name	RUBIN CLEAN CLASS 5-6 LED 6500 MICRO-PRM SH EDD IP65 34 840 KRG5DK / 620X620MM
Index	19.4109.1223.34
EAN	5902107573546



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	6679,2
LED power [W]	31
Luminaire luminous flux [lm]	4896
Power of luminaire [W]	34,7
Luminaire's light efficiency [lm/W]	141,1
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

## Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	620 x 620 x 78

## A graph of light

