

**Product:** RUBIN CLEAN CLASS 5-6 NO FRAME LED 10400 MICRO-PRM SH EDD IP65 34 830 KRG5DK / 1174X574MM

**Index:** 19.4114.1213.34



## Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

## Product information

|          |   |
|----------|---|
| Category | Clean Class 3-9   |
| Family   | RUBIN CLEAN CLASS 5-6 NO FRAME LED  |
| Name     | RUBIN CLEAN CLASS 5-6 NO FRAME LED 10400 MICRO-PRM SH EDD IP65 34 830 KRG5DK / 1174X574MM |
| Index    | 19.4114.1213.34   |
| EAN      | 5902107573935   |



## Light and electrical data


|   |  |
|---|--|
| Light source                              | LED                                    |
| Luminous flux LED [lm]                    | 10152                                  |
| LED power [W]                             | 49,6                                   |
| Luminaire luminous flux [lm]              | 7441                                   |
| Power of luminaire [W]                    | 55,6                                   |
| Luminaire's light efficiency [lm/W]       | 133,8                                  |
| Color of the light [K]                    | 3000                                   |
| CRI                                       | >80                                    |
| SDCM (LED sources)                        | 3                                      |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 89° / 89°     |
| Photobiological risk class (IEC/EN 62471) | RG0                                    |
| Protection against electric shock         | I                                      |
| Protection degree                         | IP65                                   |
| Voltage                                   | 220..240 V, 50..60 Hz                  |
| Lifetime of LED sources [h]               | 100000                                 |
| Lx/By                                     | L80/B10                                |
| Operating temperature range [°C]          | 5 ÷ 30                                 |
| Driver                                    | DIM DALI (EDD)                         |
| Power factor cos φ                        | >0,95                                  |
| Circuit load capacity                     | 14 (B10), 23 (B16), 22 (C10), 35 (C16) |

**Mechanical data**



|                  |  |
|------------------|--|
| Assembly         | surface mounted on ceiling                                       |
| Material         | steel sheet  |
| Color            | RAL 9016 (white)   |
| Diffuser         | Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass) |
| Impact resistant | IK08   |
| Dimensions [mm]  | 1174 x 574 x 69  |

**A graph of light**



**Accessories**

Index 6BZBO60980

Name Handle for pane opening

