

Product: RUBIN CLEAN CLASS 5-6 NO FRAME LED 10400 MICRO-PRM SH E IP65 34 840 KRG3K / 1174X574MM

Index: 19.4114.1221.34



Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

Product information

Category	Clean Class 3-9
Family	RUBIN CLEAN CLASS 5-6 NO FRAME LED
Name	RUBIN CLEAN CLASS 5-6 NO FRAME LED 10400 MICRO-PRM SH E IP65 34 840 KRG3K / 1174X574MM
Index	19.4114.1221.34
EAN	5901867421203



Light and electrical data


Light source	LED
Luminous flux LED [lm]	10686
LED power [W]	49,6
Luminaire luminous flux [lm]	7833
Power of luminaire [W]	55,6
Luminaire's light efficiency [lm/W]	140,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	1174 x 574 x 69

A graph of light



Accessories

Index 6BZBO60980

Name Handle for pane opening

