

Product: NUMANCIA M PRO LED 26000 SH STREET-M E IP66 12 740

Index: 19.4115.1371.12



#### **Description**

Technical floodlight for big spaces. Can be used as indoor or outdoor luminaire at high heights where top light distribution control is required. Ideal for outdoor industrial areas, loading bays, car parks, recreational sports facilities and outdoor open areas. Designed for wall surface mounted, with specific stirrup construction that eases installation. Luminaire body built in die-cast aluminium with protective hardened glass and finish in RAL 9023 (dark grey). Tool-free and fast access to inner parts. Luminaire has a high environment protection of IP65 and IK09 impact resistant, is also provided with inner pressure balancing system. Luminaire adds in an PMMA lens system and multiple optical distributions. Luminaire built-in an Electronic Control Gear.

#### **Product information**

Category	Outdoor luminaires
Family	NUMANCIA M PRO LED
Name	NUMANCIA M PRO LED 26000 SH STREET-M E IP66 12 740
Index	19.4115.1371.12
FAN	5902107371494














#### Light and electrical data

Light source	LED
Light source	
Luminous flux LED [lm]	26254,5
LED power [W]	132
Luminaire luminous flux [lm]	21347
Power of luminaire [W]	147,8
Luminaire's light efficiency [lm/W]	144,4
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP66
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-40 ÷ 35
	otomoloud on/off (E)
Driver	standard on/off (E)
Driver Power factor cos φ	>0,95




## Mechanical data





Assembly	mounted on wall
Material	aluminum
Color	RAL 9023 (dark grey)
Diffuser	SH (transparent hardened glass)
Impact resistant	IK09
Weight [kg]	7,8
Dimensions [mm]	395 x 93 x 473

# A graph of light



## **Accessories**

Index 19.2212.0001.12

Name Adapter for mounting FL2 & FL4
Numancia EP4CKINGR00001
RAL9023

