

**Product:** RUBIN CLEAN CLASS 7-8-9 LED 3900 MICRO-PRM SL EDD IP65 34 830 KRG5DK / 620X620MM

**Index:** 19.4116.2613.34



## Description

Luminaire dedicated for the clean rooms of increased cleanliness class ISO 7-8-9. Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame.

## Product information

|          |  |
|----------|--|
| Category | Clean Class 3-9  |
| Family   | RUBIN CLEAN CLASS 7-8-9 LED  |
| Name     | RUBIN CLEAN CLASS 7-8-9 LED 3900 MICRO-PRM SL EDD IP65 34 830 KRG5DK / 620X620MM |
| Index    | 19.4116.2613.34  |
| EAN      | 5902107860226  |



## Light and electrical data

|   |  |
|---|--|
| Light source                              | LED                                    |
| Luminous flux LED [lm]                    | 3807,2                                 |
| LED power [W]                             | 18,6                                   |
| Luminaire luminous flux [lm]              | 2798                                   |
| Power of luminaire [W]                    | 20,8                                   |
| Luminaire's light efficiency [lm/W]       | 134,5                                  |
| Color of the light [K]                    | 3000                                   |
| CRI                                       | >80                                    |
| SDCM (LED sources)                        | 3                                      |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 89° / 89°     |
| Photobiological risk class (IEC/EN 62471) | RG0                                    |
| Protection against electric shock         | I                                      |
| Protection degree                         | IP65                                   |
| Voltage                                   | 220..240 V, 50..60 Hz                  |
| Lifetime of LED sources [h]               | 100000                                 |
| Lx/By                                     | L80/B10                                |
| Operating temperature range [°C]          | 5 ÷ 30                                 |
| Driver                                    | DIM DALI (EDD)                         |
| Power factor cos φ                        | >0,95                                  |
| Circuit load capacity                     | 14 (B10), 23 (B16), 22 (C10), 35 (C16) |

**Mechanical data**



|                  |   |
|------------------|---|
| Assembly         | surface mounted on ceiling  |
| Material         | steel sheet   |
| Color            | RAL 9016 (white)  |
| Diffuser         | Micro-PRM SL (micro-prismatic diffuser PMMA with laminated glass) |
| Impact resistant | IK08  |
| Dimensions [mm]  | 620 x 620 x 78  |

**A graph of light**

