

**Product:** RUBIN CLEAN CLASS 7-8-9 LED 7800 SLM E IP65 840 KRG3K / 1200X600

**Index:** 19.4118.4121.34



## Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 7-8-9. Surface mounted luminary equipped in highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame.

## Product information

Category	Clean Class 3-9
Family	RUBIN CLEAN CLASS 7-8-9 LED
Name	RUBIN CLEAN CLASS 7-8-9 LED 7800 SLM E IP65 840 KRG3K / 1200X600
Index	19.4118.4121.34



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	7851
LED power [W]	39,9
Luminaire luminous flux [lm]	6290
Power of luminaire [W]	43,1
Luminaire's light efficiency [lm/W]	145,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 100° / 100,2°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 24 (C10), 38 (C16)

## Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	white
Diffuser	SLM (laminated mat glass)
Impact resistant	IK08
Dimensions [mm]	1220 x 620 x 78

## A graph of light

