

Product: AGAT CLEAN ISO NO FRAME LED CRI95 10800 SLMR E IP65 940 KRG3K / 1200X600 Index: 19.4120.3441.34




Description

Luminary is recommended to be used in medical sector to illuminate such premises as: operating rooms, rooms designed for laparoscopic and endoscopic, surgeries and interventions, recovery rooms, dermatological offices and to illuminate blood collection centres, etc. Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. This product is manufactured in production plant which holds quality management system for medical devices ISO 13485. This is a medical device. Use it in accordance with the instructions for use.

Category Recessed luminaires / CRI95 medical device Family AGAT CLEAN ISO NO FRAME LED CRI95 Name AGAT CLEAN ISO NO FRAME LED CRI95 10800 SLMR E IP65 940 KRG3K / 1200X600 Index 19.4120.3441.34 EAN 5902107014193
Name AGAT CLEAN ISO NO FRAME LED CRI95 10800 SLMR E IP65 940 KRG3K / 1200X600 Index 19.4120.3441.34 EAN 5902107014193
KRG3K / 1200X600 Index 19.4120.3441.34 EAN 5902107014193
EAN 5902107014193
Light source LED
Luminous flux LED [lm] 11750
LED power [W] 72
Luminaire luminous flux [lm] 9414
Power of luminaire [W] 73,5
Luminaire's light efficiency [lm/W] 128,1
Color of the light [K] 4000
CRI >95
SDCM (LED sources) 3
Beam angle [°] (C0-C180) / (C90-C270) - 100° / 100,2°
Protection against electric shock
Protection degree IP65
Voltage 220240 V, 5060 Hz
Lifetime of LED sources [h] 60000
Lx/By L80/B10
Operating temperature range [°C] 5 ÷ 30
Driver standard on/off (E)
Power factor $\cos \varphi$ >0,95
Circuit load capacity 9 (B10), 15 (B16), 15 (C10), 24 (C16)
Assembly mounted in module ceilings
Material steel sheet
Color white
Diffuser SLMR (laminated anti-reflective mat glass)
H Impact resistant IK08
Dimensions [mm] 1196 x 596 x 76



A graph of light



Accessories

Index 6BZBO60980



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025