

Product: AGAT CLEAN ISO NO FRAME LED CRI95 14400 SLMR E IP65 940 KRG3K / 1200X600 Index: 19.4120.3541.34




Description

Luminary is recommended to be used in medical sector to illuminate such premises as: operating rooms, rooms designed for laparoscopic and endoscopic, surgeries and interventions, recovery rooms, dermatological offices and to illuminate blood collection centres, etc. Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. This product is manufactured in production plant which holds quality management system for medical devices ISO 13485. This is a medical device. Use it in accordance with the instructions for use.

Product information	Category Boossed luminaires / CDI05 medical device
	Category Recessed luminaires / CRI95 medical device
	Family AGAT CLEAN ISO NO FRAME LED CRI95
	Name AGAT CLEAN ISO NO FRAME LED CRI95 14400 SLMR E IP65 940 KRG3K / 1200X600
	Index 19.4120.3541.34
	EAN 5902107014230
	$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{\end{array}}$
Light and electrical data	Light source LED
	Luminous flux LED [Im] 15666
	LED power [W] 99,2
	Luminaire luminous flux [lm] 12552
	Power of luminaire [W] 102,5
	Luminaire's light efficiency [Im/W] 122,5
	Color of the light [K] 4000
	CRI >95
	SDCM (LED sources) 3
	Beam angle [°] (C0-C180) / (C90-C270) - 100° / 100,2°
	Protection against electric shock I
	Protection degree IP65
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 60000
	Lx/By L80/B10
	Operating temperature range [°C] 5 ÷ 30
	Driver standard on/off (E)
	Power factor $\cos \phi$ >0,95
	Circuit load capacity 6 (B10), 10 (B16), 10 (C10), 17 (C16)
Mechanical data	Assembly mounted in module ceilings
	Material steel sheet
	Color white
	Diffuser SLMR (laminated anti-reflective mat glass)
	H Impact resistant IK08
	Dimensions [mm] 1196 x 596 x 76



A graph of light



Accessories

Index 6BZBO60980



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025