

Product: LUXCAN R 2500 13° E 63 840 3F

Index: 19.4125.2121.63



Description

Monobloc cylindrical spotlight from the family Luxcan R setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for Installation on the triphasic track. Body built in extruded aluminium painted with high quality AXALTA coatings finished in popular colours.

Product information

| Category | Projectors |
|----------|-------------------------------|
| Family | LUXCAN R |
| Name | LUXCAN R 2500 13° E 63 840 3F |
| Index | 19.4125.2121.63 |
| EAN | 5902107243173 |
















Light and electrical data

| Light source | LED |
|-------------------------------------|---|
| Luminous flux LED [lm] | 2709 |
| LED power [W] | 16,6 |
| Luminaire luminous flux [lm] | 2178 |
| Power of luminaire [W] | 18,8 |
| Luminaire's light efficiency [lm/W] | 115,9 |
| Color of the light [K] | 4000 |
| CRI | 82 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 11,6° / 13,4° |
| Protection against electric shock | I |
| Protection degree | IP20 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 77000 (1) / 100000 (2) / 100000 (3) |
| Lx/By | L90/B10 (1) / L80/B10 (2) / L70/B10 (3) |
| Operating temperature range [°C] | -20 ÷ 35 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 29 (B10), 47 (B16), 49 (C10), 79 (C16) |

Mechanical data



| Assembly | mounted on a three-phase track |
|------------------|--------------------------------|
| Material | aluminum |
| Color | RAL 9003 (white) |
| Diffuser | none |
| Impact resistant | IK04 |
| Dimensions [mm] | Ø108 x 210 |



A graph of light

