

**Product:** LUXCAN R 2500 60° E 21 840 3F

**Index:** 19.4125.2321.21



## Description

Monobloc cylindrical spotlight from the family Luxcan R setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for Installation on the triphasic track. Body built in extruded aluminium painted with high quality AXALTA coatings finished in popular colours.

## Product information


Category	<b>Projectors</b>
Family	<b>LUXCAN R</b>
Name	<b>LUXCAN R 2500 60° E 21 840 3F</b>
Index	<b>19.4125.2321.21</b>
EAN	<b>5902107247317</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>2709</b>
LED power [W]	<b>16,6</b>
Luminaire luminous flux [lm]	<b>2169</b>
Power of luminaire [W]	<b>18,8</b>
Luminaire's light efficiency [lm/W]	<b>115,4</b>
Color of the light [K]	<b>4000</b>
CRI	<b>82</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 56,2° / 53,2°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP20</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>77000 (1) / 100000 (2) / 100000 (3)</b>
Lx/By	<b>L90/B10 (1) / L80/B10 (2) / L70/B10 (3)</b>
Operating temperature range [°C]	<b>-20 ÷ 35</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>29 (B10), 47 (B16), 49 (C10), 79 (C16)</b>

**Mechanical data**



Assembly	mounted on a three-phase track
Material	aluminum
Color	RAL 9006 (grey)
Diffuser	none
Impact resistant	IK04
Dimensions [mm]	Ø108 x 210

**A graph of light**

