

Product: BERYL LED NK 2200 PLX E 34 830

Index: 19.4126.2111.34



## **Description**

Surface mounted luminary of down light type which is built from powder coated steel sheet. IP20 tightness level. Its diffuser optionally can be made from opal PMMA. BERYL LED NO/NK luminary is perfect to be used in prestige interiors such as hotels, banks, offices, boutiques, and car showrooms.

#### **Product information**

Category	Surface mounted luminaires
Family	BERYL LED NK
Name	BERYL LED NK 2200 PLX E 34 830
Index	19.4126.2111.34
EAN	5902107119188
















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	2193
LED power [W]	15
Luminaire luminous flux [lm]	1717
Power of luminaire [W]	16
Luminaire's light efficiency [lm/W]	107,3
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 79,4° / 79,2°
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	29 (B10), 47 (B16), 49 (C10), 79 (C16)

#### Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK06
Weight [kg]	1,99
Dimensions [mm]	200 x 200 x 110



# A graph of light

