

Product: BERYL LED N12/230 3000 PLX EDD IP65 34 840

Index: 19.4128.3123.34



Description

Beryl LED N12/220 luminary which is characterized by its simple compact construction and high efficiency. Luminary is highly resistant to dust and water activity what is proved by IP65 level. Luminary dedicated to be surface mounted.

Product information

Category	Outdoor luminaires	
Family	BERYL LED N12/230	
Name	BERYL LED N12/230 3000 PLX EDD IP65 34 840	
Index	19.4128.3123.34	
EAN	5902107210946	













Light and electrical data

Light source	LED
Luminous flux LED [lm]	3108
LED power [W]	16,2
Luminaire luminous flux [lm]	2277
Power of luminaire [W]	18,4
Luminaire's light efficiency [lm/W]	123,8
Color of the light [K]	4000
CRI	85
SDCM (LED sources)	2
Beam angle [°]	(C0-C180) / (C90-C270) - 99° / 97,8°
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	45000 (1) / 50000 (2) / 67000 (3)
Lx/By	L90/B10 (1) / L80/B10 (2) / L70/B10 (3)
Operating temperature range [°C]	-25 ÷ 30
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	50 (B10), 80 (B16), 61 (C10), 98 (C16)

Mechanical data





Assembly	surface mounted on ceiling
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	2,2
Dimensions [mm]	Ø120 x 230



A graph of light



