

**Product:** BERYL SURFACE LED COMPACT 1000 MICRO-PRM E 34 840

**Index:** 19.4129.1521.34



## Description

Small downlight ceiling luminaire. Several variants of the diffusers and different light distributions available. Simple assembly. Perfect for lighting corridors, reception, cloakrooms.

## Product information

Category	<b>Compact</b>
Family	<b>BERYL SURFACE LED COMPACT</b>
Name	<b>BERYL SURFACE LED COMPACT 1000 MICRO-PRM E 34 840</b>
Index	<b>19.4129.1521.34</b>
EAN	<b>5902107255084</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>1328</b>
LED power [W]	<b>8,3</b>
Luminaire luminous flux [lm]	<b>1008</b>
Power of luminaire [W]	<b>9,8</b>
Luminaire's light efficiency [lm/W]	<b>102,9</b>
Color of the light [K]	<b>4000</b>
CRI	<b>85</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 53,6° / 57°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP20</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>88000 (1) / 100000 (2) / 100000 (3)</b>
Lx/By	<b>L90/B10 (1) / L80/B10 (2) / L70/B10 (3)</b>
Operating temperature range [°C]	<b>5 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>60 (B10), 97 (B16), 101 (C10), 162 (C16)</b>

**Mechanical data**



Assembly	surface mounted on ceiling
Material	aluminum
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	Ø108 x 175

**A graph of light**

