

Product: X-LINE G/K LED 5500 PLX EDD 24 840 / L-1422MM

Index: 19.4131.7123.24



## **Description**

The group of X-line luminaries is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaries may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

## **Product information**

Category	Recessed luminaires
Family	X-LINE G/K LED
Name	X-LINE G/K LED 5500 PLX EDD 24 840 / L-1422MM
Index	19.4131.7123.24
EAN	5902107077075















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5727
LED power [W]	29
Luminaire luminous flux [lm]	3818
Power of luminaire [W]	30,5
Luminaire's light efficiency [lm/W]	125,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109° / 107,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
	( )
Lx/By	L80/B10 (1) / L70/B50 (2)
Lx/By Operating temperature range [°C]	
,	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	L80/B10 (1) / L70/B50 (2) 5 ÷ 30



		-		
$\mathbf{N}\mathbf{\Lambda}\mathbf{\Lambda}$	cha	nic	$\sim$ 1 $\sim$	1ata
IVIC	CHa		aı u	lata

Α	



Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	3,6
Dimensions [mm]	1422 x 80 x 136
Mounting hole [mm]	1412 x 70

## A graph of light

