

**Product:** X-LINE G/K LED 6600 MICRO-PRM E 24 830 / L-1702MM

**Index:** 19.4131.8211.24



## Description

The group of X-line luminaires is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaires may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

## Product information


Category	<b>Recessed luminaires</b>
Family	<b>X-LINE G/K LED</b>
Name	<b>X-LINE G/K LED 6600 MICRO-PRM E 24 830 / L-1702MM</b>
Index	<b>19.4131.8211.24</b>
EAN	<b>5902023878688</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>6608</b>
LED power [W]	<b>33,7</b>
Luminaire luminous flux [lm]	<b>4977</b>
Power of luminaire [W]	<b>35,3</b>
Luminaire's light efficiency [lm/W]	<b>141</b>
Color of the light [K]	<b>3000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 82,8° / 97,2°</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP20/44</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000 (1) / 147000 (2)</b>
Lx/By	<b>L80/B10 (1) / L70/B50 (2)</b>
Operating temperature range [°C]	<b>5 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>16 (B10), 26 (B16), 23 (C10), 37 (C16)</b>

## Mechanical data



Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	3,37
Dimensions [mm]	1702 x 80 x 136
Mounting hole [mm]	1692 x 70

## A graph of light

