

Product: X-LINE G/K LED 6600 MICRO-PRM E 24 830 / L-1702MM

Index: 19.4131.8211.24



Description

The group of X-line luminaries is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaries may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

Product information

Category	Recessed luminaires
Family	X-LINE G/K LED
Name	X-LINE G/K LED 6600 MICRO-PRM E 24 830 / L-1702MM
Index	19.4131.8211.24
EAN	5902023878688















Light and electrical data

Light source	LED
Luminous flux LED [lm]	6608
LED power [W]	33,7
Luminaire luminous flux [lm]	4977
Power of luminaire [W]	35,3
Luminaire's light efficiency [lm/W]	141
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)



$\mathbf{N}\mathbf{I}\mathbf{O}$	chai	α	data
IVIC	Liidi	IILai	data





Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	3,37
Dimensions [mm]	1702 x 80 x 136
Mounting hole [mm]	1692 x 70

A graph of light

