


Product: X-LINE G/K LED 2200 MICRO-PRM E 24 840 / L-582MM

Index: 19.4131.1221.24



Description

The group of X-line luminaries is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaries may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

Product information

Category	Recessed luminaires
Family	X-LINE G/K LED
Name	X-LINE G/K LED 2200 MICRO-PRM E 24 840 / L-582MM
Index	19.4131.1221.24
EAN	5902023878596















Light and electrical data

Light source	LED		
Luminous flux LED [lm]	2283		
LED power [W]	11,7		
Luminaire luminous flux [lm]	1720		
Power of luminaire [W]	12,6		
Luminaire's light efficiency [lm/W]	136,5		
Color of the light [K]	4000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP20/44		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000 (1) / 147000 (2)		
Lx/By	L80/B10 (1) / L70/B50 (2)		
Operating temperature range [°C]	5 ÷ 30		
Driver	standard on/off (E)		
Power factor cos φ	>0,9		
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)		



		-		
$\mathbf{N}\mathbf{I}\mathbf{A}$	cha	nic	\sim 1 \sim	1ata
IVIC	CHa		aı u	lata





Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	1,27
Dimensions [mm]	582 x 80 x 136
Mounting hole [mm]	572 x 70

A graph of light

